



ALLSTATE RUBBER TILE, WALLBASE + STAIRTREADS

sales@allstaterubber.com

www.allstaterubber.com

ALLSTATE RUBBER COVE BASE SPECIFICATIONS:

- NYC MEA #72-77-L
- Hardness: 85±5
- Gauge .125" + 0.15" (1/8")
- Dimensional stability ASTM F1861-01 No more than -0.007 inch (0.6%)
- Squareness: 90° ± .5°
- Resistance to heat aging: no fading or softening
- Recycled content: 10% standard, up to 85% upon request
- DOP free
- DEHP free (on the STATE OF CALIFORNIA list of chemicals "known to cause cancer or reproductive toxicity")
- May contribute to LEED CI and NC credit MR 4.1, MR 4.2, MR 5.1, MR 5.2
- May contribute to LEED MR 5.1 NC/CI Regional Materials: 20% manufactured regionally
- May contribute to LEED MR 4.2 Recycled Content: 20% (post consumer + ½ post industrial)
- ASTM E84-91A: Flame Spread: 50 (class b)
Smoke Density: <450
- Sizes: 2½" (63.5mm), 4" (101.6mm) & 6" (152.4mm) (6" is only available as cove base, in rolls). *Shadowbase*TM in 4 3/16" height only.
- Packed: 120' per carton (36.576m)
- Lengths: 4' (1.22m) lengths or 120' (35.576m) continuous rolls
- Formats: cove base (top set) & notoe (carpet base)
- Styles: smooth & *Shadowbase*TM
- Manufactured in Dalton, Georgia
- Matching rubber tile & Stairtread system
- 2 ½", 4" & 6" outside & outside corners available.
- Meets ASTM F1861 standard for covebase, rubber Type TP.