

Material Safety Data Sheet
FOR COATINGS, RESINS, AND RELATED MATERIALS
(Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20).

NPCA 1-72

NPCA HMIS

H = 1

F = 0

R = 0

DATE OF PREP: 06/01/2003
PREPARED BY: GREG WOOD

SECTION I

MANUFACTURED FOR: Allstate Rubber
STREET ADDRESS: 2220 S. Hamilton St. Extension
CITY & STATE: Dalton, GA ZIP CODE: 30722
EMERGENCY TELEPHONE NO.:
CHEMTREC (24 hours) 800 424-9300
AAT, Inc. (8am-5pm ET) (800) 228-4583
PRODUCT CLASS: Cove Base Adhesive
MANUFACTURER'S CODE IDENTIFICATION: CB Adhesive

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	NTP/IARC/ OSHA CARC	TLV PPM	Mg/M	LEL	VAPOR PRESSURE
NONE					

SECTION III - PHYSICAL DATA

BOILING RANGE: > 212 °F
VAPOR DENSITY : HEAVIER LIGHTER THAN AIR
EVAPORATION RATE: FASTER SLOWER THAN ETHER
PERCENT VOLATILE BY WEIGHT: 40.0 ±2.0%
WEIGHT PER GALLON: 8.5 - 8.8 lbs.
VOC EMISSION:0 g/l (Calculated per CA. South Coast Rule 1168)

SECTION IV - FIRE & EXPLOSION HAZARD DATA

DOT CATEGORY: Nonflammable FLASH POINT: n/a
LEL: Not Known
EXTINGUISHING MEDIA: Water mist, dry chemical, CO2, mechanical foam
UNUSUAL FIRE AND EXPLOSION HAZARDS: Liquid adhesive will not ignite. Dried adhesive will ignite if heated over 150°C and or exposed to ignition source, producing CO, CO2, smoke and hydrocarbons.
SPECIAL FIRE FIGHTING PROCEDURES: If dried adhesive ignites, use dry chemical, foam extinguishers, or a fog nozzle. For small fires, CO2 extinguishers can be used. Use air mask when combating dried adhesive fires.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: None Established
EFFECTS OF OVEREXPOSURE: Wet-lightheadedness, nausea, mild dermatitis. Dry-None
Acute-Eye, nose, throat irritation.
EMERGENCY AND FIRST AID PROCEDURES: Flush eyes with ample water. Wash skin with soap and water. If ingested, treat symptomatically and contact physician.

SECTION VI - REACTIVITY DATA

STABILITY: Unstable Stable
CONDITIONS TO AVOID: Closed area with open container.
HAZARDOUS DECOMPOSITION PRODUCTS: None
HAZARDOUS POLYMERIZATION: May Occur Will Not Occur
CONDITIONS TO AVOID: Strong acids or oxidants, temperatures below 35 °F

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF MATERIAL IS RELEASED OR SPILLED: Scoop up excess with shovel, wash remainder with water.

WASTE DISPOSAL METHOD: Landfill or incinerate as per local and state regulations.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Store in a cool, dry place. Optimum storage temperature 70°F.
OTHER PRECAUTIONS: Keep from freezing. Physical properties and performance may be altered if allowed to freeze. Keep sealed when not in use.
Shelf life is one year in an unopened container.