



ADHESIVE MATERIAL SAFETY DATA SHEET (MSDS): Rubber Tile Adhesive

FOR COATINGS, RESINS, AND RELATED MATERIALS (Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20).

HMIS III:

H = 1
F = 0
PH = 0

DATE OF PREP: 06/17/2004 PREPARED BY: GREG WOOD

SECTION I

MANUFACTURED FOR: Allstate Rubber
STREET ADDRESS: 2220 S. Hamilton St. Extension
CITY & STATE: Dalton, GA ZIP CODE: 30722
EMERGENCY TELEPHONE NO.: CHEMTREC (24 hours) 800 424-9300
AAT, Inc. (8am-5pm ET) (800) 228-4583
PRODUCT CLASS: Rubber Tile Adhesive
MANUFACTURER'S CODE IDENTIFICATION: RT Adhesive

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	NTP/IARC/ OSHA CARC	TLV	LEL PPM Mg/M	VAPOR PRESSURE
Ammonium hydroxide	=1.8%		50	>1

SECTION III - PHYSICAL DATA

BOILING RANGE: > 212 <F
VAPOR DENSITY: LIGHTER THAN AIR
EVAPORATION RATE: SLOWER THAN ETHER
PERCENT VOLATILE BY WEIGHT: 24-260%
WEIGHT PER GALLON: 9.8 – 10.2 lbs.
VOC EMISSION: 0 g/l (Calculated per CA. South Coast Rule 1168)

SECTION IV - FIRE & EXPLOSION HAZARD DATA

DOT CATEGORY: Nonflammable FLASH POINT: n/a
LEL: Not Known
EXTINGUISHING MEDIA: Water mist, dry chemical, CO2, mechanical foam
UNUSUAL FIRE AND EXPLOSION HAZARDS: Liquid adhesive will not ignite. Dried adhesive will ignite if heated over 150°C and or exposed to ignition source, producing CO, CO2, smoke and hydrocarbons.
SPECIAL FIRE FIGHTING PROCEDURES: If dried adhesive ignites, use dry chemical, foam extinguishers, or a fog nozzle. For small fires, CO2 extinguishers can be used. Use air mask when combating dried adhesive fires.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE: None Established
EFFECTS OF OVEREXPOSURE: Wet-lightheadedness, nausea, mild dermatitis. Dry-None
Acute-Eye, nose, throat irritation.
EMERGENCY AND FIRST AID PROCEDURES: Flush eyes with ample water. Wash skin with soap and water. If ingested, treat symptomatically and contact physician.

allstaterubber.com

Allstate Rubber 10 Malcomb Avenue | Unit 4
Teterboro, New Jersey 07608
P: 718 526 7890



ADHESIVE MATERIAL SAFETY DATA SHEET (MSDS): Rubber Tile Adhesive (Cont.)

SECTION VI - REACTIVITY DATA

STABILITY:

Unstable Stable

CONDITIONS TO AVOID:

Closed area with open container.

HAZARDOUS DECOMPOSITION PRODUCTS:

None

HAZARDOUS POLYMERIZATION:

May Occur Will Not Occur

CONDITIONS TO AVOID:

Strong acids or oxidants, temperatures below 35 <F

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF MATERIAL

IS RELEASED OR SPILLED:

Scoop up excess with shovel, wash remainder with water.

WASTE DISPOSAL METHOD:

Landfill or incinerate as per local and state regulations.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING

AND STORING:

Store in a cool, dry place. Optimum storage temperature 70°F.

OTHER PRECAUTIONS:

Keep from freezing. Physical properties and performance may be altered if allowed to freeze. Keep sealed when not in use. Shelf life is one year in an unopened container.

allstaterubber.com

Allstate Rubber 10 Malcomb Avenue | Unit 4

Teterboro, New Jersey 07608

P: 718 526 7890