



ADHESIVE MATERIAL SAFETY DATA SHEET (MSDS): Stairtread Adhesive

NPCA HMIS:

H = 1
F = 0
R = 0

DATE OF PREP: 06/01/2005 PREPARED BY: GREG WOOD

SECTION I

MANUFACTURED FOR:	Stoler Industries
STREET ADDRESS:	2220 S. Hamilton St. Extension
CITY & STATE:	Dalton, GA ZIP CODE: 30722
EMERGENCY TELEPHONE NO.:	CHEMTREC (24 hours) 800 424-9300
GENERAL INFORMATION NO.:	1-800-228-4583
PRODUCT CLASS:	Stairtread/Floor Covering Adhesive
MANUFACTURER'S CODE IDENTIFICATION:	AAT-420
TRADE NAME:	Allstate ST1, Allstate ST2

SECTION II - HAZARDOUS INGREDIENTS

None

SECTION III - PHYSICAL DATA

BOILING RANGE:	Greater than 212° F
VAPOR DENSITY :	LIGHTER THAN AIR
EVAPORATION RATE:	SLOWER THAN ETHER
PERCENT VOLATILE BY VOLUME:	40% ± 2%.
VOC EMISSION:	0 g/l (calculated per Ca. South Coast Rule 1168)

SECTION IV - FIRE & EXPLOSION HAZARD DATA

DOT CATEGORY:	Nonflammable
FLASH POINT:	N/A
LEL:	Not Known
EXTINGUISHING MEDIA:	Water mist, dry chemical, CO ₂ , mechanical foam
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Liquid adhesive will not ignite. Dried adhesive will ignite if heated over 150°C and or exposed to ignition source, producing CO, CO ₂ , smoke and hydrocarbons.
SPECIAL FIRE FIGHTING PROCEDURES:	If dried adhesive ignites, use dry chemical, foam extinguishers, or a fog nozzle. For small fires, CO ₂ extinguishers can be used. Use air mask when combating dried adhesive fires.

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:	None Established
EFFECTS OF OVEREXPOSURE:	Wet- possible lightheadedness, nausea, and/or mild dermatitis. Dry-None Acute-Eye, nose, throat irritation.
EMERGENCY AND FIRST AID PROCEDURES:	Flush eyes with ample water. Wash skin with soap and water. If ingested, treat symptomatically and contact physician.

allstaterubber.com

Allstate Rubber 10 Malcomb Avenue | Unit 4
Teterboro, New Jersey 07608
P: 718 526 7890



ADHESIVE MATERIAL SAFETY DATA SHEET (MSDS): Stairtread Adhesive (Cont.)

SECTION VI - REACTIVITY DATA

STABILITY:

Unstable Stable

INCOMPATIBILITY:

(Materials to avoid)

CONDITIONS TO AVOID:

Closed area with open container.

HAZARDOUS DECOMPOSITION PRODUCTS:

None

HAZARDOUS POLYMERIZATION:

May Occur Will Not Occur

CONDITIONS TO AVOID:

Strong acids or oxidants, temperatures below 20°F

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF MATERIAL

IS RELEASED OR SPILLED:

Scoop up excess with shovel, wash remainder with water.

WASTE DISPOSAL METHOD:

Landfill or incinerate as per local and state regulations.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING

AND STORING:

Store in a cool, dry place. Optimum storage temperature 70°F.

OTHER PRECAUTIONS:

Keep from freezing. Keep sealed when not in use. If frozen, allow adhesive to thaw at room temperature. DO NOT agitate or stir until adhesive is completely thawed. Shelf Life – One year from the date of manufactured in an unopened container.

allstaterubber.com

Allstate Rubber 10 Malcomb Avenue | Unit 4

Teterboro, New Jersey 07608

P: 718 526 7890