



"ALLSTATE RESILIENT FLOORING™, SINCE 1958"

www.allstaterubber.com

sales@allstaterubber.com

MVT/MOSAIC ADHESIVE MATERIAL SAFETY DATA SHEET

NPCA HMIS Prepared by: Tim Brown

H = 1 Date of Prep: 06/05/06

F = 0

R = 0

SECTION I

Manufactured For: Allstate Rubber Corp.

Street Address: 105-12 101st Avenue Ozone Park, NY 11416

Emergency Telephone No.: Chemtrec 1-800-424-9300

General Information No.: 1-800-228-4583

Product Class: Floor Covering Adhesive

Manufacturer's Code Identification: MVT-2 Adhesive

Trade Name: Pressure Sensitive Tile Adhesive

SECTION II — HAZARDOUS INGREDIENTS

None

SECTION III — PHYSICAL DATA

Boiling Range: > 212°F

Vapor Density: Heavier

Evaporation Rate: Slower than Ether

Percent Volatile by Volume: 49% ± 2.0

VOC Emission: 0 g/l (calculated per SCAQMD Rule 1168)

SECTION IV — FIRE AND EXPLOSION HAZARD DATA

DOT Category: Latex Emulsion

Flash Point: N.A.

LEL: Not Known

Extinguishing Media: Water mist, dry chemical, or mechanical foam

Unusual Fire and Fighting Hazards: None

Special Fire Fighting Procedures: None

SECTION V — HEALTH HAZARD DATA

Threshold Limit Value: Non-Established

Effects of overexposure: May cause eye and skin irritation after prolonged exposure.

Emergency and First Aid Procedures: Eye Contact: Wash with plenty of cold water for at least 15 minutes. Contact a physician if ingested.

SECTION VI — REACTIVITY DATA

Stability: Stable

Incompatibility: None

Conditions to avoid: Closed area with open container

Hazardous Decomposition Products: Carbon Monoxide and Carbon Dioxide by thermal decomposition

Hazardous Polymerization: Will not occur

Conditions to avoid: Not known

SECTION VII — SPILL OR LEAK PROCEDURES

Steps to be taken in case material is released or spilled: Collect in suitable container, wash area with plenty of soapy water.

Waste Disposal Method: Dispose in accordance with local, state, and federal regulations.

SECTION VIII — SPECIAL PROTECTION INFORMATION

Respiratory Protection: Proper Ventilation

Ventilation: Forced Air

Protective Gloves: Impervious gloves

Eye Protection: Safety glasses or goggles.

Other Protective Equipment: Normal work clothes

SECTION IX — SPECIAL PRECAUTIONS

Precautions to be taken in handling and storing: Store in a cool, dry place. Optimum storage temperature 70°F. Keep sealed when not in use. Shelf life: One year from date of manufacturing in an unopened container.

Other precautions: Follow good housekeeping practices. Keep from freezing. If frozen allow to thaw at room temperature. Do NOT agitate or stir while frozen.