



Allstate Rubber Corp.
Ozone Park, NYC 11416
1 718 526 7890 Fax: 1 718 849 1662
"Allstate Resilient Flooring™ Since 1958"
ALLSTATERUBBER@HOTMAIL.COM

ALLSTATE RUBBER TILE MSDS SHEET:

SECTION I: PRODUCT IDENTIFICATION:

Manufactured by: Stoler, Industries
Address: 2220 S Hamilton St Dalton, Ga 30722
Telephone: 1 718 526 7890
Product Class: sbr vulcanized rubber based floor tile
Product Identity: Allstate Rubber Tile

SECTION II: HAZARDOUS COMPONENTS:

None Known

SECTION III: PHYSICAL DATA:

Initial Boiling Point: None, this material is a solid

SECTION V: FIRE + EXPLOSION DATA:

Flash Point: NA

SECTION V: HEALTH HAZARD DATA:

Symptoms of OVER EXPOSURE inhalation: NA
Inhalation: NA
Eyes: NA
Skin: NA
Ingestion: NA

SECTION VI: REACTIVITY DATA:

Stability: Stable
Incompatibility: NA

SECTION VII: SPILL OR LEAK PROCEDURES:

Not applicable

SECTION VII: PROTECTIVE EQUIPMENT:

Not applicable

According to the Hazard Communication Standard from OSHA, MSDS's are required for all hazardous chemicals; however, the standard specifically **exempts** all "articles" from this requirement (29CFR 1910.1200 (b) (5) (IV)). "Article" by definition of the standard, is a manufactured item, which is formed to a specific shape or design during manufacture; which has end use functions dependent on its shape or design; and which does not release a hazardous chemical under normal conditions of use. All Allstate MVT falls under the "Articles" definition and therefore is exempt. Although not necessary, we have prepared the above MSDS sheet that covers all Allstate Tile products.