



[www.allstaterubber.com](http://www.allstaterubber.com)

[sales@allstaterubber](mailto:sales@allstaterubber)

### **Allstate Rubber Tile Specifications:**

- Construction; 100% vulcanized sbr rubber, Or 100% Au Natural Rubber upon demand (Allstate Au Natural Rubber tile line)
- Shore Hardness ASTM D 22 40 = 90
- Wear Resistance: DIN 430mm<sup>3</sup>. 50 Cycles CSTB.0.71cm<sup>3</sup>
- Resilience: 27%
- Elongation: 200%
- Module Resistance 60% 100kg/cm<sup>2</sup> ±10
- Electrical resistivity: 50,000 volts
- Load Limit: 560 psi (pounds per square inch)
- Sound absorption (as per DIN 52210) 2.5mm (1/8 ) gauge = 7db (A)
- ASTM E662/NFPA 258 Smoke Density. Passes + 189
- ASTM E648 Critical radiant Flux. Passes = 1.07 watts/cm<sup>3</sup>
- ASTM D 2047-93 Static Coefficient of friction = .87
- Meets ASTM F-1344 class 1.
- Moisture Standards for installation over concrete: A maximum emission of moisture vapor 3.0 pounds per 1000sq. ft per 24 hours.
- **Sizes:**
- Brasilia , Belem : 24 x 24 x 1/8 , packed 10 tiles/40 sq ft per carton.
- Les Relief s: 680 x 680mm (approx 27 x 27 =5.02 sq ft per tile).
- Confetti s/Terrazzo s: 34 x34cm (approx. 13.4 x 13.4) 55 sq ft per ctn
- AllSport 25 x 25 x 7mm.
- AllKit 27.9 x 27.9 x 10mm
- **Colors:**
- Brasilia, Belem: **100+ colors**
- Les Relief s: **80 colors**
- Confetti s/Terrazzo s: Any color combination you can think of!
- AllSport & AllKit: All Allstate D colors except for D17 + whites.
- Matching Stairtread system: Brasilia (square nose only, up to 72 in length w/ADA compliant adjustable nose. Also available w/2 contrasting abrasive safety strip for California Title 24. Belem , butts up to Brasilia Stairtread, Brasilia & Belem have the same base gauge (1/8 )
- Matching Rubber covebase in 55+ colors. Available in either **rollbase** (120 ) or stick (48 ) format, 2 ½ , 4 & 6 heights. (All A colors & selct D colors)
- Availability: Factory direct or via select distributors, call 1 718 526 7890.