ADHESIVE MATERIAL: SAFETY DATA SHEET (MSDS)

RUBBER TILE ADHESIVE

FOR COATINGS, RESINS, AND RELATED MATERIALS (Approved by U.S. Department of Labor "Essentially Similar" to Form OSHA-20).

HMIS III:
H = 1
F = 0
PH = 0

DATE OF PREP: 06/17/2004 PREPARED BY: GREG WOOD

SECTION I

MANUFACTURED FOR:	Allstate Rubber
STREET ADDRESS:	2220 S. Hamilton St. Extension
CITY & STATE:	Dalton, GA ZIP CODE: 30722
EMERGENCY TELEPHONE NO.:	CHEMTREC (24 hours) 800 424-9300 AAT, Inc. (8am-5pm ET) (800) 228-4583
PRODUCT CLASS:	Rubber Tile Adhesive
MANUFACTURER'S CODE IDENTIFICATION:	RT Adhesive

SECTION II - HAZARDOUS INGREDIENTS

INGREDIENT	NTP/IARC/ OSHA CARC	TLV PPM Mg/M	LEL	VAPOR PRESSURE
Ammonium hydroxide	=1.8%	50		>1

SECTION III - PHYSICAL DATA

BOILING RANGE:	> 212 <F
VAPOR DENSITY :	LIGHTER THAN AIR
EVAPORATION RATE:	SLOWER THAN ETHER
PERCENT VOLATILE BY WEIGHT:	24-260%
WEIGHT PER GALLON:	9.8 – 10.2 lbs.
VOC EMISSION:	0 g/l (Calculated per CA. South Coast Rule 1168)

SECTION IV - FIRE & EXPLOSION HAZARD DATA

DOT CATEGORY:	Nonflammable	FLASH POINT: n/a
LEL:	Not Known	
EXTINGUISHING MEDIA:	Water mist, dry chemical, CO_2, mechanical foam	
UNUSUAL FIRE AND EXPLOSION HAZARDS:	Liquid adhesive will not ignite. Dried adhesive will ignite if heated over 150°C and or exposed to ignition source, producing CO, CO_2, smoke and hydrocarbons.	
SPECIAL FIRE FIGHTING PROCEDURES:	If dried adhesive ignites, use dry chemical, foam extinguishers, or a fog nozzle. For small fires, CO_2 extinguishers can be used. Use air mask when combating dried adhesive fires.	

SECTION V - HEALTH HAZARD DATA

THRESHOLD LIMIT VALUE:	None Established
EFFECTS OF OVEREXPOSURE:	Wet-lightheadedness, nausea, mild dermatitis. Dry-None Acute-Eye, nose, throat irritation.
EMERGENCY AND FIRST AID PROCEDURES:	Flush eyes with ample water. Wash skin with soap and water. If ingested, treat symptomatically and contact physician.

allstaterubber.com
ALLSTATE RUBBER *by Stoler Industries*
2220 S Hamilton Extension Dalton, Georgia 30720
sales@allstaterubber.com

ADHESIVE MATERIAL: SAFETY DATA SHEET (MSDS)

RUBBER TILE ADHESIVE (continued)

SECTION VI - REACTIVITY DATA

STABILITY:	☐ Unstable ■ Stable
CONDITIONS TO AVOID:	Closed area with open container.
HAZARDOUS DECOMPOSITION PRODUCTS:	None
HAZARDOUS POLYMERIZATION:	☐ May Occur ■ Will Not Occur
CONDITIONS TO AVOID:	Strong acids or oxidants, temperatures below 35 <F

SECTION VII - SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE OF MATERIAL IS RELEASED OR SPILLED:	Scoop up excess with shovel, wash remainder with water.
WASTE DISPOSAL METHOD:	Landfill or incinerate as per local and state regulations.

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING:	Store in a cool, dry place. Optimum storage temperature 70ºF.
OTHER PRECAUTIONS:	Keep from freezing. Physical properties and performance may be altered if allowed to freeze. Keep sealed when not in use. Shelf life is one year in an unopened container.

allstaterubber.com
ALLSTATE RUBBER *by Stoler Industries*
2220 S Hamilton Extension Dalton, Georgia 30720
sales@allstaterubber.com