

SPORTS FLOOR: Highlights

Allstate Sports Floor is a strong, resilient flooring option that brings easy maintenance and wear resistance to any project. While typically thought of for gym and fitness applications, Allstate Sports Floor's colorful combinations allow for a variety of uses in any application.

Size of Tile: 39.37" x 39.37" nominal | 1000mm x 1000mm | 1m x 1m

Gauge: 8.5mm (wear layer 2.0mm)
Other gauges available - ask for details

Formats: Square Edge/Glue Down
Loose Lay/ Interlocking

RECOMMENDED ADHESIVE:
MAPEI G19, Available through a local Mapei distributor

Surface: Hammered

Warranty: 5 years

Squareness (ASTM F2055):
± 0.010 inches (± 0.254mm) is required Meets requirements

Thickness (ASTM F386):
+ 0.015/-0.005 inches (+ 0.381/- 0.127mm) is required ~0.35 inches (9 mm)

Dimensional Stability (ASTM F2199):
≤ 0.15% in both directions is required Meets requirements

Flammability (E648/NFPA 253):
≥ 0.45 watts/sq. cm for Class 1 is required Meets Class 1 (0.94)

Smoke Density (ASTM E662/NFPA 258):
< 450 is required Meets, 246 flaming and 280 non-flaming

Burn Resistance: Resistant to cigarette and solder burns

Slip Resistance (ASTM D2047): Static coefficient of friction, Leather dry 0.75, Leather wet 0.56
(not recommended for ramps)

VOC's: CA 01350 compliant

Hardness (ASTM D2240):
≥ 85 is required Shore type "A", ~ 90

Static Load (ASTM F970):
≤ 0.005 inches is required residual compression of 0.002 inches