



Sports Floor Maintenance

After Installation:

Do not perform any wet maintenance procedures for 72 hours after the installation to allow the adhesive to cure. Always post "wet floor" signs and/or "caution tape" when wet maintenance is going to be performed. Prohibit foot traffic until the floor is completely dry. Remove all metal objects prior to wetting the flooring. Follow facilities Standard Operating Procedures (SOP). All Safety Data Sheets/SDS and product label instructions must be read understood and followed prior to using the product.

Dust mop or vacuum the floor to remove dirt or grit. Note: This is the single most important maintenance activity for preserving the appearance and performance of the floor and is typically the most overlooked and omitted. Wet mop the entire floor using a suitable neutral cleaning solution like Diversey Profi or similar. Allow the solution a dwell time of approximately 10 minutes. Scrub the flooring using a suitable auto-scrubbing machine or floor scrubber (~ 175 RPM) with a red pad. For small areas, a soft nylon broom and wet vacuum may also be used. Wet vacuum up the soiled solution. Rinse with clean water. Remove using a wet vacuum, and allow the floor to dry.

Depending on the desired gloss level maintenance regime, there are many options for maintaining Sporting Life. Using Diversey Carefree® Matte Floor Finish, apply 2-3 thin coats using a flat microfiber mop. Allow drying time between each coat. The frequency for re-applying the floor finish will vary based on the application, traffic, and end-user preferences. To reapply, first, perform a "Deep Cleaning".

Daily Cleaning:

Dust mop or vacuum the floor to remove dirt or grit and follow one of the following options:

1. Damp mop using a flat microfiber mop and a suitable neutral cleaning solution like Diversey Profi or similar. Change the microfiber head often as required (after each patient room), and allow the floor to dry prior to use.
2. Large or heavily trafficked areas should use a suitable auto-scrubbing machine or floor scrubber (~ 175 RPM) with a red pad and a suitable neutral cleaning solution like Diversey Profi or similar. Scrub and wet vacuum up the soiled solution. Rinse with clean water. Remove using a wet vacuum, and allow the floor to dry prior to use.

Deep Cleaning:

This may be required when your routine cleaning is not meeting your expectations. Dust mop or vacuum the floor to remove dirt or grit. For the removal of stubborn dirt, wet scrub the floor with a neutral cleaner like Diversey Profi. This should be performed using a suitable auto-scrubbing machine or floor scrubber (~ 175 RPM) with a red pad. For small areas, a soft broom may also be used. Allow the solution a dwell time of approximately 5 minutes. Scrub and wet vacuum up the soiled solution. Rinse with clean water and allow to dry. Apply 2 thin coats of your preferred finish using a clean flat microfiber mop. Allow each coat to dry.

Note:

Do not use dust mops treated with oils or silicones, acetone, strong alkaline cleaning agents, scouring powder, strong solvents, or abrasive cleaning pads, as these can damage the product.

All policies, terms and procedures are subject to change without notice.

allstaterubber.com

Allstate Rubber 1099 Wall Street West | Suite 169
Lyndhurst, New Jersey 07071
P: 718 526 7890