

## Vent Cove Base: Specifications

### PRODUCT DESCRIPTION:

Allstate Vent Cove Base is manufactured from rubber with the highest quality additives and colorants designed to meet and exceed the performance requirements of ASTM F-1861-98, Type TS, Group 1(solid), Standard Specifications for Resilient Wall Base and Federal Specifications #SS-W-40a. Our product contains a minimum 40% recycled content & is 100% recyclable post consumer.

### DIMENSIONS:

4" high by 5/16" thick, 1/4" coved profile with a 3 1/4" long by 5/16" thick base shoe with 1/4" coved profile (nominal). Back surface machined for improved gluing surface, and square 1/8" X 1/2" vents (16 vents per 4' length) for breathability.

### FACE FINISH:

Finish shall pass the following tests and color to be -natural black 60 degree gloss-94 Pencil Hardness -4H Impact Resistance (Direct/Reverse)-160/160 IN-LB Conical Mandrel (Flex/Adhesion)-PASS QEV(3500 HR)340 UV-A ASTM D4587-Retained Gloss 60 Degree MEK Resistance (2X RUBS)->50

### HARDNESS:

ASTM D2240: Not less than 70, Shore A durometer

### FIRE RESISTANCE:

NOT RATED, naturally fire retardant material  
 CDPH v1.2 2017 VOC compliant for submittal w/ LEED 4/4.1,  
 WELL Building Standard, ANSI/GBI 01-2019 Green Globes

