



## Terrazzo8™ Data Sheet

Terrazzo8™ is a precast 1/8" terrazzo tile. It is a homogenous product consisting of natural stone or glass and a resin matrix.

### FEATURES

- 1/8" x 24" x 24" (12" x 24" available for slight upcharge).
- 20-year warranty.
- Affordable alternative to poured in place.
- Butt to joints, no grout or welding required.
- Chemical Resistance: ASTM F925. No Change.
- Custom colors: 1,000 square feet.
- Durometer Hardness: (D2240) Shore :0-100. RESULT 100.
- Fast install, using a standard flooring adhesive.
- Flexible.
- Homogeneous. Through chip construction.
- Made in the USA.
- PVC Free.
- Phthalate Free.
- Recycled Content: 18% pre-consumer, 18% post-consumer.
- Static load limit: ASTM F970 1000 PSI.
- Adhesive is Mapei Eco 373.

### POSSIBLE LEED CREDITS

- MR Credit 4 (1-2 points)
- MR Credit 5 (1-2 points)
- IEQ Credit 4.3 (1 point)

### SAFETY

- |   |                                     |
|---|-------------------------------------|
| ■ ASTM E648 Critical Radiant                | Flux Class 1 1.09 w/cm <sup>2</sup> |
| ■ ASTM E662 Smoke Density                   | Pass                                |
| ■ ASTM D2047 Static coefficient of friction | 0.80                                |
| ■ OSHA minimum 0.5, ADA (guideline) minimum | 0.6                                 |

[allstaterubber.com](http://allstaterubber.com)

Allstate Rubber 1099 Wall Street West | Suite 169  
Lyndhurst, New Jersey 07071  
P: 718 526 7890